

As per our rules, the approval of new laminates shall be requested on a case by case basis.

Rule Change Proposal

During the past years, many snipe class measurers referred about several attempts to move the jib attachment higher than the normal position, using various solutions, with the result to move the attachment forward than the maximum allowed by the rules on a horizontal plane (279mm from point 0).

To prevent those attempts and to clarify the rule and make it easier to check, the Rules Committee has submitted to the Board a proposal to change Rule 31 of the General restrictions.

This proposal shall be added to the Board agenda and, following the new "making decisions process", discussed with the final decision to be taken in September.

New rule proposal

Add to rule 31 the following paragraph:

31. All boats must have a jib stay and two side shrouds. No backstay may be used. The jib stay must be all metal 2.5mm (3/32") minimum diameter, either wire or rod and must be fastened to a tang or other deck fitting. The length of the jib stay shall be such that it does not allow the mast to touch the back of the partner when the mast is restrained only by the jib stay with shrouds and the mast push/puller off. The length of jib stay and shrouds must be incapable of being changed during a race. The forward hole of the jib fitting shall be 6mm diameter max and its centre shall be placed between 279 to 311 mm from the point 0, measured straight parallel to the base line, and no more than 45mm above the sheer line. The fitting shall be capable to be connected to the spring attachment assembly currently approved.



5