Antonio Bari - Rules Committee chairman From¹:

Email: antonio.bari9@gmail.com

Affec	cts: Constitution Deed of Gift Other		By-Laws Rules of Conduct		Class Rules NoR or SI Template
Objective: The requirement is difficult to control; it is intended to grant stiffness to the boats, but the class has the minimum weight and the MOI test rules which are sufficient to guarantee quality made boats					

Proposal (include current & proposed changed wording- changes to be shown in red): Example: By Laws: Section 1. Racing Season

The official racing sailing season of this Association shall extend for the full twelve months of the year starting on January 1st and ending on December 31st.

General Restrictions

Hull - Rule 5

Thickness of sides, transom, sides of centerboard trunk and bottom:

Fiberglass: 3mm (1/8") minimum

Fiberglass and foam sandwich or fiberglass and honeycomb sandwich:

3mm (1/8") outer skin and 1.5mm (1/16") inner skin minimum.

Wood: density of 512 kg per cubic meter (.0185 lbs. per cubic inch) or greater, 13mm (1/2") minimum. Density of less than 512 kg per cubic meter (.0185 lbs. per cubic inch), 19mm (3/4") minimum.

Plywood: 10mm (3/8") minimum.

Plywood and fiberglass: 10mm (3/8") minimum plus fiberglass.

Deck - Rule 10.

Thickness: Plywood: 6mm (1/4") minimum. Exterior grade maybe used. Fiberglass: 1.5mm (1/16"), Fiberglass and foam or honeycomb: 1.5mm (1/16") outer skin minimum.

Reasons: this requirement has never been checked; the only way to do so is to drill holes in the boats during the main championships.

Proposals can be made by the Board, Technical Committee, National Secretaries or 5 fleet captains up to 1st March.